# **TECHNICAL DATA SHEET**



# EM 1449 35% Active Cationic Emulsion of Amine Functional Polydimethylsiloxane

<b>Description</b> This product is an emulsion of amine functional polydimethylsiloxane.	Property Product	Test Method	Value
<ul> <li>Key Features</li> <li>Excellent wetting and spreading</li> <li>High molecular weight for extended performance</li> <li>APE Free</li> <li>Easily dispersed in water with minimal agitation</li> </ul>	Appearance Ionicity Solids Content (%) pH		White liquid Cationic 35 % 7.5
<ul> <li>Key Applications</li> <li>Mold release</li> <li>Leather conditioning</li> <li>Vinyl dressing</li> </ul>	Addition Rates Dosage - 1 Storage		0.5 - 5%
Rubber treatment     Application	Max Storage Temperature		40 °C / 104 °F 40 lb. pails, 441 lb. drums,
EM 1449 is a 35% cationic emulsion of an amine-functional polydimethylsiloxane. This specialty silicone polymer is delivered in an opaque, low viscosity liquid at neutral pH. This emulsion was developed as a multi-substrate release agent. Other release	Packaging Shelf Life		and 2205 lb. totes 12 mths

applications include leather conditioning, vinyl dressing and rubber treatment.

#### Use and Cure Information

To optimize the dispersion of this emulsion into the final formulation, it is recommended to add it slowly at the end of the procedure at a temperature below 40 °C (104°F) with continuous mixing or stirring

## Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

## Limitations

This product is not intended for pharmaceutical use.

Revision Date	21 Sep 2021
Revision No	9
Download Date	18 May 2024

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet.

CHT Germany GmbH: Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany

Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht-silicones.com

CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.