TECHNICAL DATA SHEET



HANSA CARE 2255 Modified organosiloxane as an ingredient for Home and Car Care.

Description

The permanently cationic charge makes these polymers excellently suited for a use as spray wax or rinse-off wax. Moreover, silicone quats may work as boosters for other substances which can then be distributed more easily on the surface.

Key Features

- Water repellency, Sheeting effect
- Cleansing effect
- Enhances gloss and color depth
- Smoothness

Key Applications

- Car Care
- Rinse Aid Formulations
- Sanitary Cleaners

Application

HANSA CARE 2255 can be used as wax additive in car shampoos, sanitary cleaners or toilet cleaners. By adding HNANSA CARE 2255, a beading effect as well as an easy-toclean effect on glass, porcelain, varnish, plastics, metal and chrome is achieved. Moreover, it is suited for formulating gloss driers, spray waxes and for "waterless car wash" products.

Health & Safety

Safety Data Sheets available on request.

Packaging

Drums and bulk containers. Please contact our sales department for more information.

Revision Date 29 Apr 2021

Revision No

Download Date 18 May 2024

Test **Property** Value Method

Product

Colourless to yellowish Appearance

liquid

Quaternary modified Chemistry organosiloxane

Ionicity Cationic

MIT Free Yes Non-Volatile Content (%)

Approx. 70 Ultralow cyclic content Yes

Viscosity Brookfield 100 - 300 cP

Addition Rates

1.0 - 5.0% in waxes Dosage - 1 2.0 - 10.0% in rinse aid Dosage - 2

formulations

0.5 - 5.0% in cleaners / Dosage - 3

shampoos

Storage

Max Storage Temperature 40 °C / 104 °F Min Storage Temperature 4 °C / 39 °F Shelf Life 6 mths