

ICM EM 1624 22% Microemulsion of a unique silicone polymer

Description

This product is a microemulsion of a unique blend of silicone polymers. These specialized polymers are designed to quickly and effectively, hydrophobe and protect a variety of automotive surfaces.

Key Features

- Adds extremely hydrophobic and protective clear coat to car surfaces
- Facilitates rapid water sheeting and beading
- Lasts up to 90 days before retreatment
- Highly dilution stable

Key Applications

- Automotive Care
- Leather
- Fabric Care
- Glass treatments

Application

ICM EM 1624 is a 22% microemulsion designed for water beading and water sheeting automotive applications. This unique microemulsion contains a blend of siloxane polymers and speciality additives. This product provides a durable hydrophobic crosslinked film, enhanced dewater and sheeting effects, high solids content, and is highly dilution stable for car wash and drying applications.

Use and Cure Information

This microemulsion can be used directly or diluted in water while maintaining pH less than 6, with any common acid, for optimal stability and effectiveness.

1. Thoroughly clean automotive surfaces before use.
2. Apply using a foam generating lance or spray bottle.
3. For maximum effectiveness allow to dwell for 1-2 minutes.
4. Rinse vigorously to activate.
5. Repeat applications for increased durability and effectiveness.

Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Limitations

This product is not intended for pharmaceutical use.

Property

Product

Appearance
Ionicity
MIT Free
Non-Volatile Content (%)
pH

Addition Rates

Dosage - 1

Dosage - 2

Dosage - 3

Storage

Max Storage Temperature
Min Storage Temperature
Packaging
Shelf Life

Test Method Value

Yellow, translucent liquid

Non-ionic

Yes

22

5

**Drying/car wash applications
diluted product up to 3000:1**

**Windshield up to 6% for hand
wipes**

**Total Body Protectant up to
1000:1**

40 °C / 104 °F

4 °C / 39 °F

**40 lb. pails, 441 lb. drums, or
2205 lb. totes**

12 mths

Revision Date 08 Feb 2022
Revision No 15
Download Date 18 May 2024

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet. CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

CHT Germany GmbH: Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany
Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht-silicones.com